

# Field Responsibilities

Updated Monday December 14, 2015 by A's Baseball .

## Barness and South Field Responsibilities

**Pitcher's mound** – holes need to be filled and tamped. If there is not enough sand, add sand.

**Pitcher's mound** –needs to be raked, hosed down covered.

**Home plate** – The holes created by batters, catchers and the ump need to be filled and tamped.

**Drain covers** - There are 3 sets of drains in the field. One set in front of catcher's box, one in front of pitcher's mound, and one in front of home plate.

**Pull then bases and put in the plugs.** Bases get put in the shed.

**Drag the field** - Run the sandpro around the field

**Base Paths** - Rake base paths and home plate. Bases paths should not be raked.

**Score board** – Turn off and put away the controller if you used it. Put the controller in the shed.

**Practice mounds** – Rake and fill in holes on both mounds – cover if there is no sand.

**Trash** – clean up

**Lock the tower** – top and bottom

**Lock the shed**

ough clay on the mound, you need to get clay from the bags in the shed a

to be filled in with clay. Same drill as the mound. It needs to be level, tam  
our dugout, one in front of the visitors' dugout and one set in the shallow

be raked side to side. They need to be raked length wise to even out the  
controller on the shelf.

e is a cover there.

and refill. There should never be a hole next to the rubber or where the pit

ipped and wet. **You cannot fill holes with in field mix.**

outfield between 3rd and 2nd. These should be covered during play but ne

dirt

acher's foot lands. **You cannot fill holes with in field mix.**

eed to be replaced with the open covers after games/practice so the field

I can drain.